



# Aqua-Bric® and Eco-Stone® Permeable Interlocking Concrete Pavements Stone Gradations

Ideal Eco-Grade Filtration Stone: Joint/Void	
Sieve Size	Percent Passing
# 4	100
# 8	49
# 16	7.3
# 60	3.6
# 100	3.5
# 200	1.6

ASTM # 9 (1/4") Stone - Joint/Void	
Sieve Size	Percent Passing
3/8"	100
No. 4	85 to 100
No. 8	10 to 40
No. 16	0 to 10
No. 50	0 to 5

ASTM # 8 (3/8") Stone - Setting Bedding	
Sieve Size	Percent Passing
1/2"	100
3/8"	85 to 100
No. 4	10 to 30
No. 8	0 to 10
No. 16	0 to 5

ASTM # 57 (3/4") Open Graded Stone - Base	
Sieve Size	Percent Passing
1 1/2"	100
1"	95 to 100
1/2"	25 to 60
No. 4	0 to 10
No. 8	0 to 5

ASTM # 467 1 1/2" Open Graded Stone - Base	
Sieve Size	Percent Passing
2"	100
1 1/2"	95 to 100
1"	35 to 70
3/4"	0 to 25

ASTM # 2 (2 1/2") Open Graded Stone - Base/Sub base	
Sieve Size	Percent Passing
3"	100
2 1/2"	90 to 100
2"	35 to 70
1 1/2"	0 to 15
3/4"	0 to 5

**Interlocking & Permeable Pavers ■ Landscape Retaining Walls ■ Garden Products**

Manufactured by **Ideal Concrete Block Company, Inc.**

45-55 Power Rd – Westford, MA 01886 • 232 Lexington St. – Waltham, MA 02452

(978) 692-3076 • fax (978) 692-0817