



# ANDOVER COLLECTION™

## SMOOTH & STONECLEFT



1 pc/set  
11" W x 16.5" L x 2.75" H



2 pcs/set  
5.5" W x 11" L x 2.75" H



2 pcs/set  
11" W x 11" L x 2.75" H

Our Andover Collection pavers offer a choice of profiles and finishes in traditional shapes scaled to complement the trend for larger paving units. Interchange styles and sizes to create a variety of eye-catching patterns, textures and details.




IdealBlock.com | info@IdealBlock.com | 800-24-IDEAL



### COLORS




Chatham Blend  
(Smooth Only)



Oxford Grey

### FINISH



Smooth



StoneCleft

### FEATURES



### APPLICATIONS



### PALLET OVERVIEW

|                   |                         |
|-------------------|-------------------------|
| PIECES PER PALLET | 27 sets/pallet          |
| PIECES PER LAYER  | 3 sets/layer            |
| PIECES PER SQFT   | 3.8 sqft/set            |
| SQFT PER PALLET   | 102.6 sqft              |
| WEIGHT PER PALLET | SM 3200 lb / SC 3100 lb |



# ANDOVER COLLECTION™



Smooth



StoneCleft

## FEATURES

- ▶ Available in Smooth or StoneCleft finish
  - Smooth surface version has minimal chamfered edges
  - StoneCleft version features a pronounced cleft and sculpted profile that replicates the look of natural stone
- ▶ Can be installed as a traditional or permeable pavement
- ▶ Made with our Color 4D Advanced Technology, Andover Collection has deeper, richer colors fortified with superior performance against the elements
- ▶ 2 3/4" thickness for improved flexural strength and weight bearing capacity
- ▶ Ideal for walkways, patios, pool decks, courtyards, residential driveways and plazas

## PHYSICAL CHARACTERISTICS

Andover Collection meets or exceeds North American industry standards, including the strength, absorption and freeze-thaw requirements. Andover Collection classifies under ASTM C1782 Standard Specification for Utility Segmental Concrete Paving Slabs..

|                          |   |
|--------------------------|---|
| Nominal Size             | 5-Piece Set: (2) 5.5" x 11" • (2) 11" x 11" • (1) 11" x 16.5" |
| Thickness                | 2 3/4" (7cm)  |
| Coverage                 | 3.8 sqft/set  |
| Percentage of Open Area  | 5.5%  |
| Compressive Strength     | 725 psi minimum   |
| Water Absorption         | 5% maximum  |
| Freeze Thaw              | No Effect   |
| Slip and Skid Resistance | Excellent to ADA  |

## PATTERNS & GUIDELINES

- ▶ Andover can be placed in our "Set-Stone" pattern that creates easy to place, impressive arrangements with little or no waste. Consisting of 5 pieces (Figure A), each set is placed as a module in a herringbone pattern. Stones within the module can be rearranged to vary the design as shown in Figure B.
- ▶ Please visit our website for complete list of patterns




Fig. B



This product is susceptible to scuffing during installation and snow removal. Protect the surface when transporting and handling. Use a roller compactor when compacting. When removing snow, the height of the snow blowers and plows must be raised or a poly blade used on the plow edge.



Deicing Advisory



Color 4D

## TECHNICAL SERVICES

Please call our sales office or visit our website for complete technical information and literature.

We also offer design consultation, specification assistance, and job-site quality review upon request.