




NEW

FAT FACE™ 2.0


Now only
65 lbs



Front



Back




Corner

8" x 18" x 10.125"

15" x 8" x 6"

Modular Versatility:

1.



Fat Face 2.0 Unit
10.125" Deep

2.



Mini Cell Unit
Fat Face 2.0 Unit - Anchor - Anchor
24" Deep

3.



Single Cell Unit
Fat Face 2.0 Unit - Trunk - Anchor
36" Deep

Fat Face 2.0 is engineered to make every installation more efficient. It's innovative design maintains the exceptional durability you expect while reducing physical strain, enhancing versatility, and significantly lowering installation costs for engineered walls. Save time, save effort, and experience the future of segmental retaining walls.




NEW FEATURES

- Fat Face 2.0 weighs only 65 lbs. That is almost 20% less than the original Fat Face unit.
- Use as a standalone wall block or create a modular system by adding our GravityStone trunks and anchors for additional stability

COLORS





Quarry Blend



Vineyard Blend

APPLICATIONS



PALLET OVERVIEW

PIECES PER LAYER	9 pieces
LAYERS PER PALLET	5 layers
PIECES PER PALLET	45
WEIGHT PER UNIT	65 lb
WEIGHT PER PALLET	3,000 lb



IdealBlock.com | info@IdealBlock.com | 800-24-IDEAL

FAT FACE™ 2.0



FEATURES

- ▶ One square foot block with split face finish
- ▶ Use as a standalone wall block or create a modular system by adding our GravityStone trunks and anchors for additional stability
- ▶ Now only 65 pounds per block - lighter than the original Fat Face
- ▶ Corner block allows for corners to be snapped at desired angle
- ▶ Up to 50% reduction in geogrid - in both layers and length
- ▶ Minimizes scope and volume of soil excavation resulting in a significant reduction in labor and equipment hours
- ▶ Suitable for residential, commercial and municipal applications
- ▶ Assemble into various cellular configurations to create a large, stable wall mass
- ▶ Create mini-cell, single-cell, multi-cell, double-sided mini-cell or double-sided single-cell assemblies and straight, concave or convex retaining walls in either a vertical or battered configuration
- ▶ When used with geogrid or trunks and anchors, walls at virtually any height can be constructed with proper engineering

PHYSICAL CHARACTERISTICS

Fat Face meets or exceeds the North American industry standard, including ASTM C 1372 Standard Specification for Drycast Segmental Retaining Wall Units. Strict quality control ensures consistent strength and durability.

Nominal Size

Single Unit	10.125" d x 8"h x 18"l
Corner Unit	6"d x 8"h x 15"l
Face Area	1 sqft/unit
Compressive Strength	3000 psi minimum
Water Absorption	13pcf maximum
Dimensional Tolerance	± 1/8"
Wall Batter	Vertical or 4.5° (1" per foot, 3/4" per course)

Modular Versatility:

- 

Fat Face 2.0 Unit
10.125" Deep
- 

Mini Cell Unit
Fat Face 2.0 Unit - Anchor - Anchor
24" Deep
- 

Single Cell Unit
Fat Face 2.0 Unit - Trunk - Anchor
36" Deep



Deicing Advisory

TECHNICAL SERVICES

Please call our sales office or visit our website for complete technical information and literature. We also offer design consultation, specification assistance, and job-site quality review upon request. Walls 4' and higher, terraced walls, and sites with weak soils, slopes and surcharges require special consideration and construction techniques, including the use of geogrid and/or GravityStone Trunks and Anchors. These conditions require the services of a qualified engineer and a professional contractor familiar with wall construction. Always comply with local building codes.