



PORTSMOUTH COBBLE™



5.5" x 5.5" | 5.5" x 6.65" | 5.5" x 7.64" | 5.5" x 8.8"

Available in four sizes and treated with Color 4D Tehnology, Portsmouth Cobble can be used as a stand-alone paver for customers who desire the look of a classic cobble walkway or driveway, or as the perfect accent to other paver styles when used as decorative banding and border courses.



IdealBlock.com | info@IdealBlock.com | 800-24-IDEAL



COLORS



Quarry Blend



Graphite

FEATURES



APPLICATIONS



PALLET OVERVIEW

PIECES PER PALLET	9 layers per pallet
PIECES PER LAYER	9 of each size per layer
SQFT PER SECTION	9.81 sqft/layer
SQFT PER PALLET	88.29
WEIGHT PER PALLET	2500 lb



PORTSMOUTH COBBLE™



FEATURES

- ▶ Comprised of four sizes with a smooth, cobbled surface and edges
- ▶ Robust spacers molded into the sides adjoin the units to form a firm, stable, interlocked pavement
- ▶ Can be used as a stand alone paver or as an accent to other paver styles
- ▶ Can be installed as a traditional or permeable pavement (variable void space)
- ▶ Made with our Color 4D Advanced Technology, Portsmouth Cobble has deeper, richer colors fortified with superior performance against the elements
- ▶ Suitable for residential, commercial and municipal applications - walkways, patios, pool decks, courtyards, driveways, plazas and pavements limited to personal vehicles


PHYSICAL CHARACTERISTICS

Portsmouth Cobble meets or exceeds North American industry standards, including the requirements of ASTM Specification C 936 for Solid Concrete Interlocking Paving Stones and CSA Standards for freeze-thaw performance. Our strict quality control ensures consistent strength, color and size.

Nominal Size	4 sizes: 5.5" x 5.5" • 5.5" x 6.65" • 5.5" x 7.64" • 5.5" x 8.8" Note: Length of all 4 sizes, placed end-to-end, is approx. 28 1/2" (14 1/4 LF per layer)
Coverage	Sold by the 9.81 sqft layer
Thickness	2.75" (7cm)
Compressive Strength	8000 psi minimum
Water Absorption	5% maximum
Freeze Thaw	No Effect
Slip and Skid Resistance	Excellent to ADA

PATTERNS & GUIDELINES

- ▶ While Portsmouth Cobble can be placed in the order of their arrangement on the pallet, the 4 different sizes are intended to replicate natural stone "settes" - achieving a faithful running bond where each course is off-set in the middle from the previous row is not necessary



4-Piece Running Bond

TECHNICAL SERVICES

Please call our sales office or visit our website for complete technical information and literature. We also offer design consultation, specification assistance, and job-site quality review upon request.



This product is susceptible to scuffing during installation and snow removal. Protect the surface when transporting and handling. Use a roller compactor when compacting. When removing snow, the height of the snow blowers and plows must be raised or a poly blade used on the plow edge.



Deicing Advisory



Color 4D