



YANKEE COBBLE™



Square
6.312" W x 6.312" L x 2.375" H



Large Rectangle
6.312" W x 9.437" L x 2.375" H



Grand Square
9.437" W x 9.437" L x 2.375" H



Circle Pak
133.5" Diameter

Yankee Cobble features pressed corners and a dimpled texture that provides a turn-of-the-century look with the stability and uniformity of precision concrete pavers.



COLORS



Quarry Blend



Vineyard Blend



Beacon Hill Blend



Graphite

*Grand Square available in Quarry Blend and Vineyard Blend

*Circle Pak available in Quarry Blend, Vineyard Blend and Graphite

APPLICATIONS



PALLET OVERVIEW

	Square	Lg. Rec	Grand Sq.	Circle Pak
PIECES PER PALLET	378	270	180	---
PIECES PER SECTION	54	54	36	---
PIECES PER SQFT	3.62	2.42	1.61	---
SQFT PER PALLET	104.42 sqft	111.57 sqft	111.8 sqft	97.21 sqft
WEIGHT PER PALLET	2950 lb	3150 lb	3225 lb	2700 lb



IdealBlock.com | info@IdealBlock.com | 800-24-IDEAL



YANKEE COBBLE™



FEATURES

- Features pressed corners and a dimpled texture that provides a turn-of-the century look
- Circle Pak allows you to integrate circles into your design
- Suitable for residential, commercial and municipal applications - walkways, driveways, patios, pool decks, sidewalks, plazas, courtyards and pavements where traffic is limited to personal vehicles

PHYSICAL CHARACTERISTICS


Yankee Cobble Pavers meet or exceed North American industry standards, including the strength, absorption, and freeze-thaw requirements of ASTM C 936 for Solid Concrete Interlocking Paving Stones. Our strict quality control ensures consistent strength, color and size.

Nominal Size


Squares	6.312" x 6.312" (160 x 160mm) • 3.62 pcs/sqft
Large Rectangles	6.312" x 9.437" (160 x 240mm) • 2.42 pcs/sqft
Grand Square	9.437" x 9.437" (240 x 240mm) • 1.61 pcs/sqft
Circle Pak	Diameter of 133.5"
Thickness	2.375" (6cm)
Compressive Strength	8500 psi minimum
Water Absorption	5% maximum
Freeze Thaw	No Effect

PATTERNS & GUIDELINES


- Can be installed in herringbone, running bond and random pattern layouts
- Packaged individually for greater design flexibility and choice, allowing you to create a variety of patterns without having unnecessary stones left over
- Please see our *Yankee Cobble™* and *MillStone™ Patterns with Style* for additional pattern options




90° Herringbone



Pattern 6



Running Bond



GS Pattern 10



This product is susceptible to scuffing during installation. Use a urethane pad attached to the compactor plate or spread a thin layer of sand or sheet of geotextile fabric over the surface when compacting.



Deicing Advisory

TECHNICAL SERVICES

Please call our sales office or visit our website for complete technical information and literature.

We also offer design consultation, specification assistance, and job-site quality review upon request.