






# WINDSOR SLAB™



Large Rectangle  
16.5" W x 33" L x 2.75" H



Small Rectangle  
8.25" W x 16.5" L x 2.75" H



Square  
16.5" W x 16.5" L x 2.75" H

Summoning the charm and elegance of old New England, the sleek, large format design allows for unlimited possibilities that rival the best features found in natural stone.



800-24-IDEAL | info@IdealBlock.com | IdealBlock.com



## COLORS



Mineral Blue

## FEATURES



## APPLICATIONS



## PALLET OVERVIEW

	Large Rectangle	Small Rectangle	Square
PIECES PER PALLET	27	108	54
PIECES PER LAYER	---	---	---
PIECES PER SQFT	.26 pcs/sqft 3.78 sqft/pc	1.06 pcs/sqft .95 sqft/pc	.53 pcs/sqft 1.89 sqft/pc
SQFT PER PALLET	102.06 sqft	102.06 sqft	102.06 sqft
WEIGHT PER PALLET	3200 lb	3225 lb	3175 lb



# WINDSOR SLAB™



## FEATURES

- ▶ Large format style with a thermal-like Natural Impressions surface, enhanced with a fortified finish
- ▶ Square edges
- ▶ "Mix-n-Match" packaging - 3 sizes individually packaged allow multiple pattern choices
- ▶ Available in Mineral Blue, an all-new color exclusive to the product
- ▶ Made with our Color 4D Advanced Technology, Windsor Slab has deeper, richer colors fortified with superior performance against the elements
- ▶ Suitable for residential, commercial and municipal applications - walkways, patios, pool decks, sidewalks, courtyards, and plazas
- ▶ Small Rectangle suitable for pedestrian and vehicular traffic limited to personal vehicles
- ▶ Large Rectangle and Square limited to pedestrian traffic

## PHYSICAL CHARACTERISTICS


Windsor Slab pavers meet or exceed North American industry standards, including the strength, absorption and freeze-thaw requirements of ASTM C 1782 for Standard Specification for Utility Segmental Concrete Paving Slabs. Our strict quality control ensures consistent strength, color and size.

### Nominal Size


Large Rectangle	16.5" x 33" • 3.78 sqft/pc
Square	16.5" x 16.5" • 1.89 sqft/pc
Small Rectangle	8.25" x 16.5" • 1.07 sqft/pc
Thickness	2.75" (7cm)
Flexural Strength	725 psi minimum
Water Absorption	5% maximum
Freeze Thaw	No Effect
Slip and Skid Resistance	Excellent to ADA

## PATTERNS & GUIDELINES


- ▶ Place different sizes randomly to create patterns similar to that of natural stone pattern stock, or choose from pre-designed patterns
- ▶ Modular size allows for other pavers in our Color 4D line to be mixed within to create intricate features, designs and borders
- ▶ Please visit our website for complete list of patterns




Pattern 1



Pattern 2



Pattern 6



Running Bond  
Random

## TECHNICAL SERVICES

Please call our sales office or visit our website for complete technical information and literature. We also offer design consultation, specification assistance, and job-site quality review upon request.



This product is susceptible to scuffing during installation and snow removal. Protect the surface when transporting and handling. Use a roller compactor when compacting. When removing snow, the height of the snow blowers and plows must be raised or a poly blade used on the plow edge.



Deicing Advisory



Color 4D