



NEW

BROOKLINE SLAB



16.5" W x 27.5" L x 2.75" H

Featuring a clean, smooth surface and refined minimal chamfers, the large-format Brookline Slab delivers a bold, contemporary aesthetic. Designed to stand confidently on its own or integrate seamlessly with our Andover Collection Smooth, it offers designers and contractors exceptional flexibility for cohesive, modern designs.

IDEAL
PAVERS | WALLS | ELEMENTS

IdealBlock.com | info@IdealBlock.com | 800-24-IDEAL



COLORS



Oxford Grey

FEATURES



APPLICATIONS



PALLET OVERVIEW

PIECES PER PALLET	30
PIECES PER LAYER	3
PIECES PER SQFT	3.15 sqft/pc 0.32 pc/sqft
SQFT PER PALLET	94.5 sqft
WEIGHT PER PALLET	3000 lb



BROOKLINE SLAB



FEATURES

- ▶ Smooth surface enhanced with a fortified finish and minimal chamfered edges
- ▶ Can be used as a stand-alone paver or integrated with Andover Collection and Andover GrandStone
- ▶ Made with our Color 4D with Advanced Technology, the Andover GrandStone has deeper, richer colors fortified with superior performance against the elements
- ▶ 2 3/4" thickness for improved flexural strength and weight bearing capacity
- ▶ Ideal for pedestrian applications in residential, commercial and municipal projects - walkways, patios, pool decks, sidewalks, courtyards, plazas


PHYSICAL CHARACTERISTICS

Brookline Slab pavers meet or exceed North American industry standards, including the strength, absorption and freeze-thaw requirements of ASTM C 1782 Standard Specification for Utility Segmental Concrete Paving Slabs.


Nominal Size	16.5" x 27.5" • 3.15 sqft/pc
Thickness	2 3/4" (7cm)
Percentage of Open Area	7.5%
Flexural Strength	725 psi minimum
Water Absorption	5% maximum
Freeze Thaw	No Effect
Slip and Skid Resistance	Excellent to ADA

PATTERNS & GUIDELINES


- ▶ Can be installed in a variety of patterns including running bond or integrated into our Andover Collection set-stone pattern and Andover GrandStone.
- ▶ *Please visit our website for complete list of patterns*



1:1 Brookline Slab & Andover Collection



Herringbone



Running Bond



This product is susceptible to scuffing during installation and snow removal. Protect the surface when transporting and handling. Use a roller compactor when compacting. When removing snow, the height of the snow blowers and must be raised.



Deicing Advisory



Color 4D

TECHNICAL SERVICES

Please call our sales office or visit our website for complete technical information and literature. We also offer design consultation, specification assistance, and job-site quality review upon request.